




ZAHNSTANGEN FÜR FORTLAUFENDE MONTAGE - EINGRIFFSWINKEL 20°

RACKS-CONTINUOUS MOUNTING - PRESSURE ANGLE 20°



Werkstoff Stahl C45

Modul x Nennlänge	Ist-Länge	Zähnezahl	B x ha	ho	kg
1 x 500	499,51	159	15 x 15	14	0,80
1 x 1000	1002,17	319	15 x 15	14	1,60
1 x 2000	2001,19	637	15 x 15	14	3,30
1,5 x 500	499,51	106	17 x 17	15,5	1,00
1,5 x 1000	1003,74	213	17 x 17	15,5	2,10
1,5 x 2000	2002,77	425	17 x 17	15,5	4,10
2 x 500	502,65	80	20 x 20	18	1,40
2 x 1000	1005,31	160	20 x 20	18	2,80
2 x 2000	2004,34	319	20 x 20	18	5,60
2,5 x 500	502,65	64	25 x 25	22,5	2,20
2,5 x 1000	1005,31	128	25 x 25	22,5	4,40
2,5 x 2000	2002,77	255	25 x 25	22,5	8,70
3 x 500	499,51	53	30 x 30	27	3,20
3 x 1000	1008,45	107	30 x 30	27	6,30
3 x 2000	2007,48	213	30 x 30	27	12,60
4 x 1000	1005,31	80	30 x 30	26	6,00
4 x 2000	2010,62	160	30 x 30	26	12,10
4 x 500	502,65	40	40 x 40	36	5,60
4 x 1000	1005,31	80	40 x 40	36	11,20
4 x 2000	2010,62	160	40 x 40	36	22,40
5 x 500	502,65	32	50 x 50	45	8,70
5 x 1000	1005,31	64	50 x 50	45	17,50
5 x 2000	2010,62	128	50 x 50	45	35,00
6 x 1000	1017,88	54	60 x 60	54	25,20
6 x 2000	2016,90	107	60 x 60	54	50,40